



3.9L 4D34 ENGINE

Built for the long run. Reliable performance comes hand in hand with power and fuel efficiency.



ANTI-LOCK BRAKING SYSTEM (ABS) and Automatic Brake Adjustor



ABS help to maintain control of the vehicle during emergency braking situations, and enable proper steering around obstacles.

IN DASH GEARSHIFT



Easier operation and comfortable driving position. Provides ample leg room for easy shift from driver-seat to assistant-seat.



INTERIOR



New seat design with wide seat adjustment to provide comfortable driving position.



Simple, compact & functional dashboard. Ergonomic arrangement of switchers, levers and open storage space.



New stylish and easy-to-read instrument cluster.



Impact absorption steering column.



Central locking and power window.

EXTERIOR



06 Side marker lamp.



Headlamp levelling provide optimum headlamp and light projection distance. Comes with day time running lamp.



Reverse sensor for easy reverse operation.




6mm chassis





Tubeless tyre providing longer tread life and gentle deflation in case of puncture.



Fuso RISE Body with door impact beam, front box structure and reinforced cab floor main sill.

TECHNICAL SPECIFICATION



	MODEL R.H.D		FE83PE6SRDG3 - 7.5	FE83PG6SRDG3 - 7.5	FE85PG6SRDG3	
	Max G.V.W.	kg	7,500	7,500	7,500	
WEIGHT	Front axle	kg	1,615	1,640	1,640	
	Rear axle	kg	760	780	780	
	Kerb weight approx.	kg	2,375	2,420	2,420	
	Wheelbase (W.B.)	mm	3,350	3,850	3,850	
	Overall length (O.A.L.)	mm	6,015	6,735	6,735	
CINCIONS	Overall width (O.A.W.)	mm	2,035	2,035	2,035	
i	Overall height (O.A.H.)	mm	2,195	2,195	2,195	
	Tread Front (T.F.)	mm	1,665	1,665	1,665	
	Rear (T.R.)	mm	1,560	1,560	1,560	
	Ground clearance approx. (G.C.)	mm	195	195	195	
	Cab to rear axle (C.A.)	mm	2,825	3,325	3,325	
	Cab to end frame (C.E.)	mm	4,305	5,025	5,025	
	Frame width (F.W.)	mm	753	753	753	
	Front overhang (F.O.H.)	mm	1,145	1,145	1,145	
	Rear overhang (R.O.H.)	mm	1,480	1,700	1,700	
ENGINE	Model		Mitsubishi 4D34-2AT4 turbocharge with intercooler			
	Туре	-	4-stroke, water-cooled, direct injection diesel engine			
	No. of cylinders	-	4 in line			
	Piston displacement	cc	3,908			
	Max. output	kW(PS)@rpm	100(136)@2,900			
	Max. torque	Nm@rpm	370@1,600			
	Air cleaner		Dry paper element type			
	Alternator	Volt	24V - 50Amps			
ш	Clutch	Туре	Hydraulic control, single dry plate			
		mm		300		
DRIVELINE	Transmission		M035S5 5 forward and 1 reverse speed, manual, overdrive 2nd to 5th range; Synchromesh gears 1st & Rev. range; Constantmesh gears			
	Gear ratios		5.38-3.028-1.700-1.00-0.722-Reverse 5.380			
	Final reduction gear		Single reduction, hypoid gear			
	Ratio	-	6.166			
,	Seating capacity	-	3			
CABIL	Cabin tilt	2	Mechanical			
5	Power windows		Equipped			
51	Central lock & alarm system		Equipped			
	Reverse sensors & buzzer	-	Equipped			
	Kangaroo bar		Equipped			
0	Axle type/Rating	Front	Reverse elliot, "I" beam type			
CHASSIS	The state of the s	Rear	Full floating type			
	Tyres	Studs	6			
	13.44	Tyre Size	215/75R17.5			
	Steering	Tyle Size	Right hand steering. Ball nut type with integral type hydraulic power booster.			
	- Coloring		Telescopic and tilt steering column with steering lock			
	Suspension	Front				
	Ouspension	Rear	Laminated leaf springs with shock absorbers Main and auxiliary laminated leaf springs with shock absorbers			
	Brake Service		Hydraulic with vacuum servo assistance, dual circuit with antilock brake system (ABS) & auto brake shoes adjuster			
		Parking				
		Parking	Internal expanding type on propeller shaft			
	Fuel tenk	Auxiliary	Exhaust brake			
	Fuel tank		100 liters			
	Electrical system	*	12 Volt x 2, 65Ah at 20 hr. rate			

FUSO Financial

FUSO Financial – A Daimler Financial Services
Brand. The financial services provided by
Mercedes-Benz Services Malaysia Sdn Bhd are
regulated by the provisions of the Financial Services
Act 2013. Mercedes-Benz Services Malaysia's
operations are not within the regulatory purview of
Bank Negara Malaysia.

MITSUBISHI FUSO authorised dealer:

100,000km OR 3 YEARS WARRANTY



MITSUBISHI FUSO authorised distributor:
Mercedes-Benz Malaysia Sdn Bhd (596096-H)
Wisma Mercedes-Benz, 16A Jalan BK 1/13,
Taman Perindustrian Bandar Kinrara,
47180 Puchong, Selangor Darul Ehsan.
Tel: +603-8074 1188 I Fax: +603-8074 1199
www.fuso.my